

> PERSONAL LIGHTS



> MEDIUM DUTY LIGHTS



> MEDIUM DUTY LIGHTS



> TACTICAL LIGHTS



> TACTICAL LED LIGHTS



> NEMO DIVE SERIES



> LED AND RECOIL LIGHTS



> LED AND RECOIL LIGHTS



> HEADLIGHTS



> SPECIALTY LIGHTS



> HEAVY DUTY LIGHTS



> REMOTE AREA LIGHTING SYSTEMS



> SPECIFICATIONS AND FEATURES

CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUNTIME	ANSI BEAM DISTANCE	ANSI PEAK BEAM INTENSITY	ANSI WATERPROOF/SUBMERSIBLE/WATER RESISTANT	APPROVALS	COLORS
1900	2 AAA Alkaline*	1.6 oz. (0.05)	4.09" (10.4)	11	1h 30m	45m	571cd	IPX7	CI D1	■ ■ ■ ■ ■
1910	1 AAA Alkaline*	1.4 oz. (0.04)	3.6" (9.1)	39	1h	62m	967cd	IPX4	N/A	■
1920	2 AAA Alkaline*	2.2 oz. (0.06)	5.3" (13.5)	67	2h 45m	81m	1648cd	IPX4	N/A	■
1960	2 AAA Alkaline*	1.9 oz. (0.05)	5.48" (13.9)	24	3h	51m	657cd	IPX7	N/A	■ ■
1965	2 AAA Alkaline*	1.9 oz. (0.05)	5.48" (13.9)	21	4h	51m	756cd	IPX4	CI II III D1	■ ■ ■
2140	2 AAA Alkaline*	1.8 oz. (0.05)	3.5" (8.9)	13	2h	84m	1761cd	IPX7	CID2	■
2250	2 AA Alkaline	0.3 oz. (0.09)	3.87" (9.8)	7	5h 30m	54m	726cd	IPX4	CI II D2	■
2300	2 AA Alkaline*	3.4 oz. (0.1)	5.62" (14.3)	11	4h 30m	43m	478cd	IPX4	CI D1	■ ■ ■
2340	2 AA Alkaline**	3.5 oz. (0.1)	6.25" (15.9)	10	4h 30m	43m	461cd	IPX4	CI D1	■ ■ ■
1800	2 C Alkaline	7.8 oz. (0.22)	6" (15.2)	21	7h	131m	4370cd	IPX7	CI II D2	■ ■ ■ ■
1820	2 C Alkaline**	8.3 oz. (0.24)	5.83" (14.8)	22	6h 45m	146m	5466cd	IPX7	CI II III D2	■ ■ ■ ■ ■
2000	3 C Alkaline	12.8 oz. (0.36)	7.79" (19.8)	53	5h	158m	6234cd	IPX7	CI D2	■ ■ ■ ■ ■
2400	4 AA Alkaline*	7.1 oz. (0.2)	6.49" (16.5)	45	3h 45m	125m	3934cd	IPX7	CI D1	■ ■ ■ ■ ■
2430	4 AA Alkaline*	6.1 oz. (0.17)	6.5" (16.5)	70	2h 15m	104m	2766cd	IPX4	CI D2	■ ■ ■ ■ ■
2450	Rechargeable 4 AA NiMH*	7.8 oz. (0.22)	6.5" (16.5)	35	3h 30m	122m	3735cd	IPX7	CI II D2	■ ■ ■ ■ ■
2320	2 CR123 Lithium*	5.6 oz. (0.16)	5.51" (14)	82	1h 15m	145m	5260cd	IPX4	N/A	■ ■ ■ ■ ■
3320	2 CR123 Lithium*	3.45 oz. (0.1)	5.27" (13.4)	81	1h 30m	131m	4330cd	IPX4	N/A	■ ■ ■ ■ ■
3390	2 CR123 Lithium*	3.45 oz. (0.1)	5.27" (13.4)	81	1h 30m	131m	4330cd	IPX4	N/A	■ ■ ■ ■ ■
8040	4 C Alkaline	18.4 oz. (0.52)	11.25" (28.6)	67	5h 15m	198m	9820cd	IPX4	CI II III D2	■ ■ ■ ■ ■
8050	Rechargeable 4 C NiCad*	17.92 oz. (0.51)	11.25" (28.6)	137	1h 30m	234m	13,707cd	IPX4	N/A	■ ■ ■ ■ ■
2330	2 CR123 Lithium*	5.5 oz. (0.16)	5.51" (14)	100	6h	93m	2184cd	IPX4	N/A	■ ■ ■ ■ ■
2360	2 AA Alkaline	4.6 oz. (0.13)	6.1" (15.5)	94	2h 15m	139m	4893cd	IPX4	N/A	■ ■ ■ ■ ■
2390	2 CR123 Lithium*	5.6 oz. (0.16)	5.31" (13.5)	177	2h 30m	155m	6002cd	IPX4	N/A	■ ■ ■ ■ ■
3330	2 CR123 Lithium*	3.45 oz. (0.1)	5.27" (13.4)	90	4h 45m	88m	1959cd	IPX4	N/A	■ ■ ■ ■ ■
7060	Rech. 3.7v, 2200mAh Lithium-Ion*	10.4 oz. (0.29)	8.65" (22)	160	2h	254m	16,101cd	IPX4	N/A	■ ■ ■ ■ ■
8060	Rechargeable 4 C NiMH*	23.2 oz. (0.66)	12.67" (32.2)	179	6h 45m	279m	19,525cd	IPX4	N/A	■ ■ ■ ■ ■
1900N	2 AAA Alkaline*	1.6 oz. (0.05)	4.09" (10.4)	11	1h 30m	45m	571cd	IPX8	N/A	■ ■ ■ ■ ■
1960N	2 AAA Alkaline*	1.9 oz. (0.05)	5.48" (13.9)	24	3h	51m	657cd	IPX8	N/A	■ ■ ■ ■ ■
2000N	3 C Alkaline	12.8 oz. (0.36)	7.79" (19.8)	53	5h	158m	6234cd	IPX8	N/A	■ ■ ■ ■ ■
2010N	3 C Alkaline	13.4 oz. (0.38)	8.11" (20.6)	56	43h	74m	1359cd	IPX8	N/A	■ ■ ■ ■ ■
2400N	4 AA Alkaline*	7.1 oz. (0.2)	6.49" (16.5)	45	3h 45m	125m	3934cd	IPX8	N/A	■ ■ ■ ■ ■
2410N	4 AA Alkaline*	7.3 oz. (0.21)	7" (17.8)	72	7h 15m	102m	2622cd	IPX8	N/A	■ ■ ■ ■ ■
4300N	8 C Alkaline	36.64 oz. (1.04)	7.5" (19)	276	6h	143m	5222cd	IPX8	N/A	■ ■ ■ ■ ■
1830	3 AAAA Alkaline*	1.2 oz. (0.03)	6.2" (15.7)	5	32h	13m	44cd	IPX4	CI D1	■ ■ ■ ■ ■
1930	4 LR 44 Alkaline*	0.9 oz. (0.03)	2.64" (6.7)	12	4h 15m	17m	70cd	IPX4	CI D1	■ ■ ■ ■ ■
2010	3 C Alkaline	13.4 oz. (0.38)	8.11" (20.6)	56	43h	74m	1359cd	IPX7	CI II III D1	■ ■ ■ ■ ■
2020	3 C Alkaline	14.7 oz. (0.42)	8.75" (22.2)	75	6h 30m	113m	3211cd	IPX4	CI II D1	■ ■ ■ ■ ■
2130	2 L1154 Alkaline*	0.5 oz. (0.01)	1.73" (4.4)	4.7 (non ANSI)	130h (non ANSI)	N/A	N/A	IPX7	N/A	■
2130IR	2 L1154 Alkaline*	0.5 oz. (0.01)	1.73" (4.4)	N/A	65h (non ANSI)	N/A	N/A	IPX7	N/A	■
2220	2 CR2032 Lithium*	1 oz. (0.03)	3.5" (8.9)	9	34h	12m	38cd	IPX4	CI D1	■ ■ ■ ■ ■
2220NV	2 CR2032 Lithium*	1 oz. (0.03)	3.5" (8.9)	1.0 (non ANSI)	100h (non ANSI)	N/A	N/A	IPX4	CI D1	■ ■ ■ ■ ■
2365	2 AA Alkaline	9.3 oz. (0.26)	21.92" (55.7)	49	7h	81m	1644cd	IPX4	N/A	■ ■ ■ ■ ■
2410	4 AA Alkaline*	7.3 oz. (0.21)	7" (17.8)	72	7h 15m	102m	2622cd	IPX7	CI II III D1	■ ■ ■ ■ ■
2460	Rechargeable 4 AA NiMH*	7.8 oz. (0.22)	7" (17.8)	73	4h 15m	99m	2454cd	IPX7	CI II D2	■ ■ ■ ■ ■
2490	4 AA Alkaline	8.2 oz. (0.23)	12.5" (31.7)	51	15h	88m	1930cd	IPX7	N/A	■ ■ ■ ■ ■
3610	4 AA Alkaline*	10.5 oz. (0.3)	7.51" (19.1)	72	7h 15m	102m	2622cd	IPX7	CI II III D1	■ ■ ■ ■ ■
3660	Rechargeable 4 AA NiMH*	10.56 oz. (0.3)	7.51" (19.1)	73	4h 15m	99m	2454cd	IPX4	CI II D2	■ ■ ■ ■ ■
2600	4 AA Alkaline*	9.7 oz. (0.27)	3.81" (9.7)	18	3h 30m	27m	203cd	IPX7	CI II III D2	■ ■ ■ ■ ■
2610	3 AAA Alkaline*	3.2 oz. (0.09)	1.49" (3.8)	30	19h	28m	194cd	IPX4	CI D1	■ ■ ■ ■ ■
2620	3 AAA Alkaline*	4.8 oz. (0.14)	2.16" (5.5)	14*, 26**	2h 15m* 18h**	44m* 29m**	491cd* 216cd**	IPX4	CI D1	■ ■ ■ ■ ■
2640	4 AA Alkaline*	10.9 oz. (0.31)	2.63" (6.7)	16*, 29**	2h 45m* 17h**	46m* 20m**	586cd* 103cd**	IPX4	CI D2	■ ■ ■ ■ ■
2680	4 AA Alkaline*	9.7 oz. (0.27)	4.64" (11.8)	69	9h 30m	123m	3788cd	IPX7	CI II III D2	■ ■ ■ ■ ■
2690	3 AAA Alkaline*	4.1 oz. (0.12)	2.81" (7.1)	60	10h 30m	81m	1664cd	IPX4	CI II III D1	■ ■ ■ ■ ■
3700	4 C Alkaline	20.32 oz. (0.58)	7" (17.8)	25*, 39**	6h 15m 8h 30m***	98m 51m***	2437cd 684cd***	IPX4	CI D2	■ ■ ■ ■ ■
3750	Rechargeable 4 C NiCad*	20.48 oz. (0.58)	7" (17.8)	28*, 96**	1h 45m 4h***	133m 65m***	4468cd 1048cd***	IPX4	CI D2	■ ■ ■ ■ ■
4000	8 D Alkaline	74.08 oz. (2.1)	9.37" (23.8)	251	11h	106m	3168cd	IPX4	CI II D2	■ ■ ■ ■ ■
9410	Rechargeable 4 D NiMH*	49.28 oz. (1.4)	8.75" (22.2)	300*, 710**	1h 45m* 4h 45m**	425m* 249m**	45,260cd* 15,516cd**	IPX4	N/A	■ ■ ■ ■ ■
CAT NO.	BATTERIES	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	LUMENS	RUNTIME	BEAM SPREAD	NUMBER OF LEDS	LAMP HEADS	APPROVALS	COLORS
9430	12V Rechargeable, Sealed*	22.65 lbs. (10.27)	32.28" (82)*	1000*, 2000**	15h*, 8h**	90°	24 per head	1	N/A	■ ■
9430IR	12V Rechargeable, Sealed*	22.05 lbs. (10)	32.28" (82)*	N/A	15h*, 8h**	7°	24 per head	1	N/A	■
9430SL	12V Rechargeable, Sealed*	22.05 lbs. (10)	32.28" (82)*	1000*, 2000**	15h*, 8h**	10°	24 per head	1	N/A	■
9435	Rechargeable NiMH*	17.6 lbs. (7.98)	32.28" (82)*	750*, 1500**	10h*, 5h**	90°	28 per head	1	CI D1	■ ■ ■ ■ ■
9440	Rechargeable NiMH*	16.09 lbs. (7.3)	86.25" (219)*	1200*, 2400**	6h*, 3h**	120°	10 per head	1	N/A	■ ■ ■ ■ ■
9460	12V Rechargeable, Sealed*	50.71 lbs. (23)	70.87" (179.9)*	2000*, 4000**	14h*, 7h**	90°	24 per head	2	N/A	■ ■ ■ ■ ■
9470	12V Rechargeable, Sealed*	88.18 lbs. (40)	72.85" (185)*	4000*, 8000**	14h*, 7h**	90°	24 per head	4	N/A	■ ■ ■ ■ ■
9500	N/A	29.8 lbs. (13.52)	20.62" (52.4)	400*, 2000**	constant 120V	210° (diffused)	36 per head	3	N/A	■ ■ ■ ■ ■

Rechargeable lights